

EX30

- Rated engine HP 16.9 kW (23.0 PS)
- Operating weight Canopy: 2 700 kg (5 950 lb)
Cabin: 2 830 kg (6 240 lb)
- Backhoe bucket PCSA heaped: 0.046 — 0.111 m³
(0.06 — 0.14 cu yd)
CECE heaped: 0.04 — 0.095 m³



AUTOMATIC CONTROL OF POWER AND SPEED IS POSSIBLE

- OHS for smooth combined operations.
- Variable displacement pump permitting automatic control of power and speed.
- The maximum speed in this class realized by two-speed travel.
- Light and easily controllable hydraulic pilot-type control lever.
- Low noise design best-suited for work in urban areas.
- Small turning radius suited for narrow space.
- Bucket clearance adjustment device.
- Gate lock lever to be never left unlocked.

ENGINE

Model	ISUZU 3KR2
Type	Water-cooled, 4 cycle, 3 cylinder direct injection type diesel engine
Rated flywheel horsepower (DIN 6271, net)	16.9 kW (23.0 PS) at 2 200 rpm
Fated flywheel horsepower (SAE J1349, net)	16.9 kW (22.7 HP) at 2 200 rpm
Maximum torque	81.4 N-m (8.3 kgf-m, 69.4 lbf-ft) at 1 800 rpm
Piston displacement	1.422 l (86.7 cu in)
Bore and stroke	81 mm x 92 mm (3.2" x 3.6")
Batteries	1 x 12 V, 52 AH

HYDRAULIC SYSTEM

OHS (Optimum Hydraulic System)

This system with two variable displacement pumps gives high independence to each actuator for easy and smooth combined operation. Such as travel/blade, travel/swing, travel/arm and swing/arm. Especially, combined operation of swing and arm is very useful when vertically digging the sides of trenches.

Main pumps	2-variable displacement axial piston pump
Maximum oil flow	2 x 36.0 l/min (2 x 9.5 US gpm, 2 x 7.9 Imp gpm)
Pilot pump	1-Gear pump
Maximum oil flow	8.8 l/min (2.3 US gpm, 1.9 Imp gpm)

Relief Valve Settings

Implement circuit	20.6 MPa (210 kgf/cm ² , 2 986 psi)
Swing circuit	10.3 MPa (105 kgf/cm ² , 1 493 psi)
Travel circuit	20.6 MPa (210 kgf/cm ² , 2 986 psi)
Pilot circuit	3.9 MPa (40 kgf/cm ² , 569 psi)

Hydraulic Cylinders

High-strength piston rods and tubes. Cylinder cushion mechanisms provided in boom and boom swing cylinders to absorb shocks at stroke ends.

Dimensions

	Quan.	Bore	Stroke
Boom	1	80 mm (3.1")	565 mm (1' 10")
Arm	1	75 mm (3.0")	560 mm (1' 10")
Bucket	1	65 mm (2.6")	440 mm (1' 5")
Boom swing	1	75 mm (3.0")	435 mm (1' 5")
Blade	1	90 mm (3.5")	140 mm (5.5")

CONTROLS

Pilot controls (for front and swing operations), light touch and excellent controllability

SUPERSTRUCTURE

Swing Mechanism

High-torque, axial piston motor with planetary reduction gear is bathed in oil. Swing circle is single-row, shear-type ball bearing with induction-hardened internal gear. Internal gear and pinion gear are immersed in lubricant. Swing shockless valve built in swing motor absorbs shocks when stopping swing, ensuring smooth stops. Also counter balanceless system is employed for smooth operation when starting and stopping swing. Swing lock (pin lock type) is provided for transporting.

Swing speed	10.3 min ⁻¹ (10.3 rpm)
Boom swing angle	Canopy Left: 90°, Right: 50° Cabin Left: 80°, Right: 50°

Operator's Cab (Factory Option)

Independent roomy cab, conforming to ISO* Standards. Reinforced glass windows on all 4 sides for all-round visibility. Front window (upper side), fully openable, are spring-assisted for easy storing in the cab and for absorbing shocks during lowering.

*International Standard Organization

UNDERCARRIAGE

Tracks

Tractor-type undercarriage. Heavy-duty track frame of all welded structure. Top-grade materials employed for heavy-duty operation. Side frames are rigidly welded to the track frame. Rugged track frame and sloped side frames for easy mud removal.

Numbers of Rollers and Shoes on Each Side

Upper rollers	1
Lower rollers	4
Track shoes	42

Traction Device

Each track driven by a high-torque, axial piston 2 speed travel motor through planetary reduction gear, allowing counterrotation of the tracks. Travel shockless relief valve built in travel motor absorbs shocks when stopping travel, ensuring smooth stops.

Travel speeds	High: 0 to 4.2 km/h (2.61 mph) Low: 0 to 3.0 km/h (1.86 mph)
Maximum traction force	18.6 kN (1 900 kgf, 4 180 lbf)
Gradeability	30° (58%) continuous

WEIGHTS AND GROUND PRESSURE

Equipped with 2.38 m (7' 10") boom, 1.27 m (4' 2") arm and 0.092 m³ (0.12 cu yd: PCSA heaped) bucket.

Shoe type	Shoe width	Standard undercarriage	
		Operating weight	Ground pressure
Rubber (canopy)	300 mm (11.8")	2 630 kg (5 786 lb)	24.5 kPa (0.25 kgf/cm ² , 3.6 psi)
	300 mm (11.8")	2 760 kg (6 072 lb)	25.5 kPa (0.26 kgf/cm ² , 3.7 psi)
*Double grouser (canopy)	300 mm (11.8")	2 700 kg (5 940 lb)	25.5 kPa (0.26 kgf/cm ² , 3.7 psi)
	300 mm (11.8")	2 830 kg (6 226 lb)	26.5 kPa (0.27 kgf/cm ² , 3.8 psi)
Double wide grouser (canopy)	400 mm (15.7")	2 800 kg (6 160 lb)	26.5 kPa (0.27 kgf/cm ² , 3.8 psi)
	400 mm (15.7")	2 930 kg (6 446 lb)	27.5 kPa (0.28 kgf/cm ² , 3.98 psi)
Triangular (canopy)	400 mm (15.7")	2 820 kg (6 204 lb)	26.5 kPa (0.27 kgf/cm ² , 3.8 psi)
	400 mm (15.7")	2 950 kg (6 490 lb)	27.5 kPa (0.28 kgf/cm ² , 3.98 psi)

*Mark is standard specification.

SERVICE REFILL CAPACITIES

	liters	US gal	Imp gal
Fuel tank	50	13.2	11.0
Engine coolant	5.0	1.3	1.1
Engine oil	5.5	1.5	1.2
Travel final device (each side).....	0.5	0.13	0.11
Hydraulic tank	40	10.5	8.8

Buckets

Capacity m ³ (cu yd)		Width mm (ft in)		No. of teeth	Weight kg (lb)	Recommendation	
PCSA heaped	CECE heaped	Without side cutters	With side cutters			2.38 m (7' 10") arm	1.57 m (5' 2") arm
0.046(0.06)	0.04	260(10.2")	300(11.8")	2	47(103.4)	○	○
0.057(0.07)	0.05	310(12.2")	350(13.8")	3	50(110)	○	○
0.074(0.10)	0.065	410(16.1")	450(17.7")	3	55(121)	○	○
*0.092(0.12)	0.08	480(18.9")	520(20.5")	4	60(132)	○	□
0.111(0.14)	0.095	560(22")	600(23.6")	4	68(149.6)	□	△
A: Arm crowd force				kN (kgf, lbf)		15.7 (1 600, 3 520)	14.1 (1 440, 3 168)
B: Bucket digging force				kN (kgf, lbf)		20.6(2 100, 4 620)	

*Marks are standard specifications

- Suitable for materials with density of 2 000 kg/m³ (3 370 lb/cu yd) or less
- Suitable for materials with density of 1 600 kg/m³ (2 700 lb/cu yd) or less
- △ Suitable for materials with density of 1 100 kg/m³ (1 850 lb/cu yd) or less

CANOPY TYPE

LIFTING CAPACITIES

Side: Rating over-side or 360 degrees

Front: Rating over-front

With dozer blade above ground

Unit: ton (lb)

Condition	Load point height m(ft in)	Load radius						At max. reach		
		2 m (6'7")		3 m (9'10")		4 m (13'2")		Side	Front	@m(ft in)
		Side	Front	Side	Front	Side	Front			
Boom: 2.38 m (7'10")	3 (9'10")			*0.48 (1 056)	*0.48 (1 056)			0.31 (682)	0.35 (770)	4.10 (13'5")
Arm: 1.27 m (4'2")	2 (6'7")			0.52 (1 144)	0.59 (1 298)	0.31 (682)	0.36 (792)	0.25 (550)	0.29 (638)	4.53 (14'10")
Bucket	1 (3'3")			0.48 (1 056)	0.56 (1 232)	0.30 (660)	0.35 (770)	0.23 (506)	0.27 (594)	4.62 (15'2")
PCSA: 0.092 m ³ (0.12 cu yd)	0 (Ground)			0.45 (990)	0.52 (1 144)	0.29 (638)	0.34 (748)	0.25 (550)	0.29 (638)	4.42 (14'6")
CECE: 0.08 m ³	-1 (-3'3")	0.84 (1 848)	1.01 (2 222)	0.44 (968)	0.52 (1 144)			0.31 (682)	0.36 (792)	3.85 (12'8")
Grouser shoe 300 mm (11.8")	-2 (-6'7")	0.86 (1 892)	1.04 (2 288)	0.45 (990)	0.53 (1 166)					


With dozer blade on ground

Unit: ton (lb)


Condition	Load point height m(ft in)	Load radius						At max. reach		
		2 m (6'7")		3 m (9'10")		4 m (13'2")		Side	Front	@m(ft in)
		Side	Front	Side	Front	Side	Front			
Boom: 2.38 m (7'10")	3 (9'10")			*0.48 (1 056)	*0.48 (1 056)			0.31 (682)	*0.51 (1 122)	4.10 (13'5")
Arm: 1.27 m (4'2")	2 (6'7")			0.52 (1 144)	*0.59 (1 298)	0.31 (682)	*0.55 (1 210)	0.25 (550)	*0.53 (1 166)	4.53 (14'10")
Bucket	1 (3'3")			0.48 (1 056)	*0.84 (1 848)	0.30 (660)	*0.62 (1 364)	0.23 (506)	*0.56 (1 232)	4.62 (15'2")
PCSA: 0.092 m ³ (0.12 cu yd)	0 (Ground)			0.45 (990)	*1.02 (2 244)	0.29 (638)	*0.69 (1 518)	0.25 (550)	*0.59 (1 298)	4.42 (14'6")
CECE: 0.08 m ³	-1 (-3'3")	0.84 (1 848)	1.59 (3 498)	0.44 (968)	*0.98 (2 156)			0.31 (682)	*0.61 (1 342)	3.85 (12'8")
Grouser shoe 300 mm (11.8")	-2 (-6'7")	0.86 (1 892)	1.05 (2 310)	0.45 (990)	*0.68 (1 496)					

- Notes: 1. Rating are based on SAE J1097.
2. Lifting capacity does not exceed 75% of tipping load with the machine on firm, level ground or 87% of full hydraulic capacity.
3. The load point is a hook (not standard equipment) located on the back of the bucket.
4. *Indicates load limited by hydraulic capacity.

DIMENSIONS



WORKING RANGES



CABIN TYPE

LIFTING CAPACITIES

Side: Rating over-side or 360 degrees

Front: Rating over-front

With dozer blade above ground

Unit: ton (lb)

Condition	Load point height m(ft in)	Load radius						At max. reach		
		2 m (6'7")		3 m (9'10")		4 m (13'2")		Side	Front	@m(ft in)
		Side	Front	Side	Front	Side	Front			
Boom: 2.38 m (7'10")	3 (9'10")			*0.48 (1 056)	*0.48 (1 056)			0.34 (748)	0.39 (858)	4.10 (13'5")
Arm: 1.27 m (4'2")	2 (6'7")			0.56 (1 232)	0.59 (1 298)	0.34 (748)	0.39 (858)	0.27 (594)	0.32 (704)	4.53 (14'10")
Bucket	1 (3'3")			0.52 (1 144)	0.60 (1 320)	0.33 (726)	0.38 (836)	0.26 (572)	0.30 (660)	4.62 (15'2")
PCSA: 0.092 m ³ (0.12 cu yd)	0 (Ground)			0.49 (1 078)	*1.02 (2 244)	0.32 (704)	0.37 (814)	0.27 (594)	0.31 (682)	4.42 (14'6")
CECE: 0.08 m ³	-1 (-3'3")	0.91 (2 002)	1.10 (2 420)	0.48 (1 056)	0.56 (1 232)			0.34 (748)	0.39 (858)	3.85 (12'8")
Grouser shoe 300 mm (11.8")	-2 (-6'7")	0.93 (2 046)	1.05 (2 310)	0.49 (1 078)	0.58 (1 276)					


With dozer blade on ground

Unit: ton (lb)


Condition	Load point height m(ft in)	Load radius						At max. reach		
		2 m (6'7")		3 m (9'10")		4 m (13'2")		Side	Front	@m(ft in)
		Side	Front	Side	Front	Side	Front			
Boom: 2.38 m (7'10")	3 (9'10")			*0.48 (1 056)	*0.48 (1 056)			0.34 (748)	*0.51 (1 122)	4.10 (13'5")
Arm: 1.27 m (4'2")	2 (6'7")			0.56 (1 232)	*0.59 (1 298)	0.34 (748)	*0.55 (1 210)	0.27 (594)	*0.53 (1 166)	4.53 (14'10")
Bucket	1 (3'3")			0.52 (1 144)	*0.84 (1 848)	0.33 (726)	*0.62 (1 364)	0.26 (572)	*0.56 (1 232)	4.62 (15'2")
PCSA: 0.092 m ³ (0.12 cu yd)	0 (Ground)			0.49 (1 078)	*1.02 (2 244)	0.32 (704)	*0.69 (1 518)	0.27 (594)	*0.59 (1 298)	4.42 (14'6")
CECE: 0.08 m ³	-1 (-3'3")	0.91 (2 002)	*1.59 (3 498)	0.48 (1 056)	*0.98 (2 156)			0.34 (748)	*0.61 (1 342)	3.85 (12'8")
Grouser shoe 300 mm (11.8")	-2 (-6'7")	0.93 (2 046)	*1.05 (2 310)	0.49 (1 078)	*0.68 (1 496)					


- Notes: 1. Rating are based on SAE J1097.
2. Lifting capacity does not exceed 75% of tipping load with the machine on firm, level ground or 87% of full hydraulic capacity.
3. The load point is a hook (not standard equipment) located on the back of the bucket.
4. *Indicates load limited by hydraulic capacity.

DIMENSIONS






WORKING RANGES





- 1 Fail-safe gate lock lever**
With the fail-safe gate lock levers, the control levers can be locked without fail, allowing access to the operator's seat.
- 1 Hydraulic pilot control levers**
Front and swing control levers are hydraulically pilot-controlled for light and comfortable operation. What more, ergonomically designed lever grip enhances operating ease and comfort.
- 2 Body cover protection weight**
A body may be protected from damage by any external shock during operation.
- 3 Engine key stop of car feeling**
With the adoption of stop motor, an engine may be stopped only by turning the key off. Moreover the engine hood or fuel cap can be locked and unlocked with the engine key.
- 4 Easy-to-read monitor panel**
With the monitor panel, the operator can check machine conditions of a glance from his seat.



- 5 Easy engine access**
The engine cover opens completely to allow easy access during engine maintenance.
- 6 Compact traction mechanism**
Compact yet sturdy travel mechanism, with travel piping provided within track frame.
- 7 Bucket clearance adjust mechanism**
It can easily eliminate loose movement of the bucket by merely replacing the shim. O-ring seal is provided at the pin, located at the arm top, to seal out dirt, extending lubricating intervals.

These specifications are subject to change without notice.

Hitachi Construction Machinery Co., Ltd.

Head Office: Nippon Bldg., 6-2, 2-chome, Ohtemachi,
Chiyoda-ku, Tokyo 100, Japan

Telephone: Tokyo (03) 3245-6361

Facsimile: Tokyo (03) 3246-2606

Telex: J32539 HITACONJ

Cable Address: "TOKHITACHIKENKI"